

PRODUCT SPECIFICATION

IMC 352 - PHOS COPPER
C12220



Copper ⁽¹⁾	99.95 MIN%
Iron	0.003 MAX%
Sulfur	0.003 MAX%
Lead	0.002 MAX%
Antimony	0.002 MAX%
Nickel	0.002 MAX%
Arsenic	0.001 MAX%
Tin	0.002 MAX%
Total Other ⁽²⁾	0.010 MAX%
Phosphorus	0.040 – 0.065 %

(1) Copper includes Silver and Phosphorus

(2) Other metallic elements include: Bi, Cd, Mn, Hg, Se, Te, Zn

SIZES

PHOS COPPER BALLS

19mm / .75"
25mm / 1.00"
31mm / 1.25"
40mm / 1.60"
45mm / 1.80"
48mm / 1.90"
50mm / 2.00"
55mm / 2.20"

PACKAGING

- 44 lb Boxes / 20 Kg
2200 lb Pallets / 1000 Kg
- 220 lb Drums / 100 Kg
1980 lb Pallets / 900 Kg
- 50 lb Pails / 22.7 Kg
1600 lb Pallets / 726 Kg
- Bulk Packaging Available

FEATURES

- Hot rolling produces a fine-grained structure.
- Uniform Phos distribution reduces sludging.
- Consistent surface area and consistent dissolution.
- Quick-settling characteristics avoid bridging, voids and basket damage.
- Perfect for automated chute loading.
- For use in any anode basket or tray.
- Special process eliminates precleaning.
- Color-coded, user-friendly packaging.
- Certificate of Analysis issued for every lot.

TYPICAL APPLICATIONS

- Printed Circuits
- Plated on Plastic Trim
- Decorative Plating
- Electronic Components
- Corrosion Protection in Automotive Parts
- Electrical Connectors
- Power Distribution Equipment
- Ammunition
- Coinage
- Rotogravure Cylinders

CAS NUMBER: 7440 – 50-8 / MSDS NUMBER: 2007

This information herein is believed to be reliable, however, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose. The manufacturer shall not be liable to damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patents.

135 Old Boiling Springs Road • Shelby, NC 28152